



Photometric Lighting Plan
SCALE: 1" = 30'-0"

Statistics

Location	mark	Avg. fc	Max. fc	Min. fc	Avg. to Min.
Parking Lot	+	1.7	11.0	0	1.6 to 1
Building Perimeter	+	7.8	9.8	4.3	2.3 to 1

Parking Lot & Building Perimeter Lighting Fixtures

Symbol	Qty.	Description	Lamp	Model No.	Notes
WP1	20	Atlas Fixture Exterior Wall Mounted Wall Pack Type	120 / 277 v 64 Watts	WLD64LED3K	Building Perimeter Light
POLE1	2	Atlas Eagle Series Pole mounted LED Shielded	120 / 277 v 100 Watts	lamp is 24L 24,000 lumens	Pole: SSS20511TEB5 14' Mounted Height Shielded (RV Parking)
SPOT	2	WAC Lighting Landscape LED Spot & Flood Light	12 v 16 Watts	WACP124298	Ground Sign Light



Applicant: **HILLEMANN**
CONSTRUCTION COMPANY
734-478-4294
Joe@hilemannconstruction.com
2370 E. Stadium Blvd. #835
Ann Arbor, MI 48104

Architect: **Gannon Architecture LLC**
2041 N. Arbor Way Dr. #73
Canton, MI 48188
ph: 734-709-7568
mgannon_4@msn.com

Project & Owner:
Site Plan Review for:
Aviana Self-Storage
406 West Main Street
Stockbridge, MI 49285
734-478-4294

Sheet Title:
Photometric Plan

Date: 12-12-14
Rev. 1 8-3-20

Sheet Number:
S-3